

## Accessories and Lenses

<b>Supplied Accessories</b>	Remote control, power cord, computer cable, 2 AA batteries, lens cover, USB wireless adapter cover, application CD, user's manual CD, user's manual
<b>Optional Accessories</b>	USB Wireless Adapter, TB-1 wireless pen tablet
<b>Replacement Parts</b>	
<b>Lamp</b>	DT01511
<b>Remote Control</b>	HL03035
<b>Filter</b>	UX37191

## Projection Throw Chart (In inches)

Screen Size 16:10		Throw Distance
Diagonal	Width	
60	51	19.7
70	59	23.4
80	68	27.1
90	76	30.8
100	85	34.5

Throw Ratio: (distance : width) 0.4 : 1

## Specifications

<b>Display</b>	<b>Projection Technology</b>	3LCD, 3 chip technology
	<b>Resolution</b>	XGA 1024 x 768
	<b>White Light Output</b>	3,200 ANSI lumens
	<b>Color Light Output</b>	3,200 ANSI lumens
	<b>Colors</b>	16.7 million colors
	<b>Aspect Ratio</b>	Native 4:3 and 16:9 / 16:10 compatible
	<b>Contrast Ratio</b>	10,000 : 1 (using active IRIS)
<b>Lens &amp; Operation</b>	<b>Throw Ratio</b> (distance : width)	0.4 : 1
	<b>Focus Distance</b>	18" - 50"
	<b>Display Size</b>	60" - 150"
	<b>Lens</b>	f = 5.65 mm
	<b>Lamp Wattage</b>	225W
<b>Compatibility</b>	<b>Expected Lamp Life*</b>	Approximately 5,000 hours (standard mode) 10,000 hours (Eco-2 mode)
	<b>Expected Filter Life**</b>	Approximately 4,000 hours
	<b>Speaker Output</b>	16W
<b>Connectors</b>	<b>Keystone</b>	H and V: +/- 5°
	<b>Computer</b>	VGA, SVGA, XGA, WXGA/WXGA+/SXGA/SXGA+/UXGA (compressed), MAC 16"
	<b>H-Sync</b>	15 kHz - 106 kHz
	<b>V-Sync</b>	50 Hz - 120 Hz
	<b>Composite Video</b>	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	<b>Component Video</b>	480i, 480p, 576i, 720p, 1080i, 1080p
	<b>HDMI</b>	480i, 480p, 576i, 720p, 1080i, 1080p, computer signal TMDS clock 27 MHz - 150 MHz
<b>Ratings &amp; Warranty</b>	<b>Digital Input</b>	HDMI x 2 (HDCP compliant)
	<b>Computer Input 1</b>	15-pin mini D-sub x 1
	<b>Computer Input 2</b>	15-pin mini D-sub x 1
	<b>Computer Monitor Output</b>	15-pin mini D-sub x 1
	<b>Video Input</b>	
	S-Video	N/A
	Composite Video	RCA jack x 1
	Component Video	15-pin mini D-sub x 2, (shared with computer in 1/2)
	<b>Audio Input</b>	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1
	<b>Audio Output</b>	3.5 mm stereo mini jack x 1
<b>Connectors</b>	<b>Network LAN Wired</b>	RJ-45 port (10 base-T / 100 base-TX)
	<b>Network LAN Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required
	<b>USB</b>	Type A x 2 (PC-less presentation, wireless adapter) Type B x 1 (USB display or mouse control)
	<b>Control Terminals</b>	9-pin mini D-sub x 1 (RS-232 control)
	<b>Power Supply</b>	AC90-132V / AC198-264V, 50/60Hz
	<b>Power Consumption</b>	340W
	<b>Operating Temperature</b>	32°F - 104°F (0°C - 40°C)
	<b>Dimensions (W x D x H)</b>	13.6" x 11.9" x 3.4" (excl. protruding parts)
	<b>Weight</b>	Approximately 8.4 lbs
	<b>Approvals</b>	UL 60950-1 / cUL FCC Part 15 subpart B Class B
<b>Ratings &amp; Warranty</b>	<b>Warranty</b>	3 year limited parts and labor. Extended Service Contract available (additional cost)

\* Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

\*\* Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

# CP-BX301WN

HI0394-05/15

All specifications subject to change without notice.  
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.  
iPad and iPhone are registered trademarks of Apple Inc., registered in the U.S. and other countries.  
©2015 Hitachi America, Ltd. All Rights Reserved.

**Hitachi America, Ltd.**

Toll Free: 1.800.HITACHI • Email: [dmd.info@hal.hitachi.com](mailto:dmd.info@hal.hitachi.com)  
Web: [hitachi-america.us/projectors](http://hitachi-america.us/projectors)

