


84" MULTI Touch LED LCD



TRIUMPH BOARD 84" MULTI Touch LED LCD is a fully integrated, professional, multi touch **4K/2K** LED LCD with amazing performance and stunning visuals.

TRIUMPH BOARD 84" MULTI Touch LED LCD is an effective presentations tool for showing lessons or presentations interactively in any classroom and meeting room. The IR LED optical technology allows six finger touch, up to six users to write and draw simultaneously using fingers, stylus or even a pointer.

The optional built-in MINI PC with incorporated Intel® Core™ i5 and i7 Processors and Microsoft® Windows® 8.1 Pro (OEM) with a selection of language options and preinstalled applications, delivering top-of-the-line performance for a zero-compromise experience.

A wide range of accessories such as LiftBoxes or mobile stands makes a perfect solution!

Features

- Multi-Touch (6 Touch Input)
- 4K/2K resolution (3840 x 2160)
- Android system
- Optional Build in MINI PC
- Optional LiftBoxes and Stands
- TRIUMPH CLOUD – the online annotation software with cloud data storage
- TB Comenius Lite – the instant desktop annotation software
- Display Note – the collaboration software (Cloud)
- MyScript Stylus – the handwriting recognition software for easy and keyboard-free typing into any text field, in any application
- RM Easiteach Next Generation - the comprehensive educational and teaching software

Specifications

Display

EAN:	8592580111853
Screen Type:	TFT LCD/A Standard/LED backlight
Resolution:	ULTRA HD (3840 x 2160 px)
Display Area:	1860,48 (H) x 1046,52 mm (V)
Display Color:	1,07 B (10 - bit)
Diagonal size:	2134,61 mm
Brightness:	350 cd/m2
Contrast:	1600 : 1
Response Time:	5 ms
Refreshing Frequency:	120 Hz
View Angle:	178°/178° (H/V)
Service Life:	50.000 hrs
Mount System:	VESA 600 x 600 (Optional)
Outline Dimension:	2006 x 1192 x 107 mm
Package Dimension:	2170 x 1460 x 320 mm
Net/Gross weight:	118/156 kg

Ambient Conditions

Operation Temperature:	0° - 40°C
Operation Humidity:	10 - 90% RH
Storage Temperature:	-10° - 60°C
Storage Humidity:	10 - 95% RH

Touch System

Touch Input:	6 Touch Input
Sensing Type:	Infrared Transmission (multi-touch)
Response Time:	< 20 ms (typ)
Scan Frequency:	200 Hz
Output Coordinates:	32767 x 32767
Communication Mode:	Full-speed USB
Writing Facility:	Opaque objects of any diameter
(Single point)	≥ 5mm
Writing Facility:	Opaque objects of any diameter
(Multi point)	≥ 8mm
Writing Screen:	Mohs hardness of 7
Life Time:	> 80 000 hours

PC System: PC6A/PC7A (Optional)

Sound System

Power Amplify:	2 x 15 W
Number of Sound Box:	2
Sound:	Surround

Power

Power Requirements:	100~240 V AC 50/60 Hz
Overall Power Consumption:	< 565 W
Standby Power Consumption:	≤ 0.5 W

Inputs and Outputs

HDMI IN:	4*
VGA-OUT:	1
Coax OUT:	1
AUDIO OUT:	1
Audio IN:	3
VGA IN:	3
USB 3.0:	1
USB 2.0:	1
Touch OUT:	1
LAN (RJ45):	1
RS 232:	1
AC IN:	1
Power:	1
CVBS:	1
R/L (CVBS):	1

*HDMI: 1x HDMI 4K
1x HDMI MHL
2x HDMI

